

The Control Pedestal U23/23 accommodate the devices necessary for control and monitoring. Ready wired, it can be quickly and easily installed on the sea deck. The housing (pedestal head) is made of seawater-resistant aluminium.

Surface treatment:
Priming and structure-finishing paint
Standard colour RAL 7032 pebble-grey



Technical data:

Operation temperature	-40°C to +85°C
Degree of protection	IP66

	U23/23	N61.../N62...	H / PW / 2D	PQ	KLV	X
Housing						
U23/23	With 1 narrow cover with pillar-gasket					
U23/23A	With 1 narrow cover without drilling in the housing					
IA	Monitoring devices cover with gasket for max. 2 monitors 72 x 72 mm or 4 monitors 72 x 36 mm and max. 6 indicating devices pos. 28, 29					
RS	Pillar 108mm Ø 670 mm height with flange quadratic or round					
Masterswitch / Control-Switch						
N61	HG Masterswitch with ball handle and indicating labels					
N62	KN Control-Switch with knob and indicating label					

		-HG	-01 Z P	-A05	P134	-X
Axis 1: direction 3-4						
(Standard contacts gold-plated 2A 250 V AC15)						
01	2 contacts	Standard contact - arrangement see page 122				
02	4 contacts	z.B.				
03	6 contacts	A05	MS21			
04	8 contacts	A0500	MS21-00			
<i>A99 contact - arrangement according customer request</i>						
Z	Spring return					
R	Friction brake					
P	Potentiometer	P131	T396 2 x 0,5 kOhm	I max. 1 mA		
		P132	T396 2 x 1 kOhm	I max. 1 mA		
		P133	T396 2 x 2kOhm	I max. 1 mA		
		P134	T396 2 x 5 kOhm	I max. 1 mA		
		P135	T396 2 x 10 kOhm	I max. 1 mA		
<i>More potentiometers on request!</i>						

U23/23 / N61.../N62... / H / PW / 2D / PQ / KLV / X

Command and indicating devices		
H	Heating	20 Watt 220 or 110V 50/60 Hz
PV	Mushroom head push button latching	22 latching with indicating label 1 Ö
P	Mushroom head push button	22 with indicating label 1 S
D	Push button	22 with indicating label 1 S
W	Selector switch 0-1	22 with indicating label 1 S
L	Indicator light	22 with indicating label Diode 24 Volt
L	Indicator light	22 with indicating label Diode 230 Volt AC
	Contact block additional	1 S or 1 Ö
L	Indicator light	22 with indicating label Diode 24 Volt protection IP65
L	Indicator light	10 with indicating label Diode 24 Volt protection IP65
Display devices		
PQ	Powermeter PQ 72 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 1 mA DC illuminated 24 Volt	Engraved your instructions
PQ	Powermeter PQ 72 x 36 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 x 36 1 mA DC illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 100/200/1A illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 x 36 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 x 36 100/200/1A illuminated 24 Volt	Engraved your instructions
Wiring		
KLV on terminal block 2,5 mm ² with wire line 0,75 mm ²		
Special model		
X	Special / customer specified	

